

INDUSTRIAL COMPONENT DATA

PLD E 608-CA-MS/1,0/FS AM 2702304 PHOENIX CONTACT

Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLD E 608-CA-MS/1,0/FS AM



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLD E 608-CA-MS/1,0/FS AM
Catalog number	2702304
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-0FE19ECE02
Generated	2026-08-04

Product Overview

Power cable

Power cable, 3-pole, PVC, orange RAL 2004, Straight male connector, coding: black, to Straight connection female, coding: black, cable length: 1 m

Power cable, 3-pole, PVC, orange RAL 2004, cable length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Control Systems (CST)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2702304

Packing unit 1 pc

Catalog page Page 486 (C-6-2017)

GTIN 4055626112299

Weight per Piece (excluding packing) 130.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 1 m

Ambient conditions

Degree of protection IP20

IP40 (plugged in)

General

Rated current at 40°C 16 A

Rated voltage 250 V AC

Number of positions 3

Coding black

Insertion/withdrawal cycles 100

Material

Material, knurls not available

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127049000eCl@ss 6.027279200eCl@ss 7.027279218eCl@ss 8.027279218eCl@ss 9.027060311

ETIM 5.0EC002556ETIM 6.0EC001855

UNSPSC 13.231251501

ETIM for 2702304 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

3

Cable length (EF000536)

1 m

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

No

Cable type (EF000081)

Multi-core

Vulcanize (EF004115)

No

Rated current In (EF008250)

16 A

Rated voltage (EF000228)

250 V

Degree of protection (IP) (EF005474)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLD E 608-CA-MS/1,0/FS AM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.