

**INDUSTRIAL COMPONENT DATA**

# ME 22,5 UT/FE BUS/ 5+2 KMGY 2201856 PHOENIX CONTACT

## Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 UT/FE BUS/ 5+2 KMGY



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME 22,5 UT/FE BUS/ 5+2 KMGY      |
| Catalog number  | 2201856                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-CCFAD5D951                    |
| Generated       | 2026-08-05                       |

## Product Overview

Electronic housing

Rail box, Bottom of the box with metal pin, with FE contact, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 107.3 mm, color: light gray (7035), cross bridge: integrated bus connector, number of poles cross connector: 5+2, Bus connector: 5 parallel contacts, 2 series contacts

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2201856

Packing unit 10 pc

Note Made to Order (non-returnable)

GTIN 4046356990653

Weight per Piece (excluding packing) 55.240 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Housing type Component housing

Housing material Polyamide

Color (RAL) light gray

**Ambient conditions**

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

**Dimensions**

Length 99 mm

Height 114.5 mm

Width 22.5 mm

Depth 99 mm

102 mm

**Technical data**

Connection in acc. with standard CUL

Nominal voltage UN 300 V

Nominal current IN 8 A

Indicator1 CUL1

Number of positions 16

4

**Standards and Regulations**

Connection in acc. with standard CUL

Flammability rating according to UL 94 V0

**Environmental Product Compliance**

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**

eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 4.0EC000886ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 13.231261501

ETIM for 2201856 Low-voltage industrial controls and switchgear (EC002779)

**Feature Name****Feature Value**

Type of enclosure (EF003086)

Closed

Housing connectable (EF003088)

No

Material (EF002169)

Other

Surface finishing (EF006569)

Other

Colour (EF000007)

Grey

RAL-number (EF000116)

7035

Width (EF000008)

22.6 mm

Height (EF000040)

99 mm

Depth (EF000049)

107.3 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 UT/FE BUS/ 5+2 KMGY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.