

INDUSTRIAL COMPONENT DATA

PLT-EE-T3-24DC-R 1249054 PHOENIX CONTACT Type 3 surge protection, consisting of plug-in protection and screw..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLT-EE-T3-24DC-R



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLT-EE-T3-24DC-R
Catalog number	1249054
Category	Surge protection device for terminal equipment
Minimum order	1 Pcs
Document ID	EO-71A623BD03
Generated	2026-08-06

Product Overview

Type 3 surge protection, consisting of plug-in protection and screw-connected base element, with integrated status indication and remote signal for single-phase power grids. Rated voltage: 24 V AC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

ETIM for 1249054 Earthing, lightning and surge protection (EC000942)

Feature Name

Feature Value

Max. continuous voltage AC (EF004198)

34 V

Voltage protection level L-N (EF004236)

0.2 kV

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Max. conductor cross section solid (solid, stranded) (EF008827)

4 mm²

Max. conductor cross section flexible (fine-strand) (EF008828)

2.5 mm²

With remote signalling contact (EF000422)

Yes

Signalling at the device (EF004241)

Optic

Category type 3 (EF004231)

Yes

Degree of protection (IP) (EF005474)

IP20

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLT-EE-T3-24DC-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.