

INDUSTRIAL COMPONENT DATA

PLT-SEC-T3-120-P-UT/PT 2907922 PHOENIX CONTACT Type 3 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLT-SEC-T3-120-P-UT/PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLT-SEC-T3-120-P-UT/PT
Catalog number	2907922
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-4BE89ACDA6
Generated	2026-08-04

Product Overview

Type 3 surge protection plug

Replacement connector for type 2/3 surge protection from the PLT-SEC-...-UT/PT product series. Nominal voltage 120 V.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)
--------------	---------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2907922

Packing unit 10 pc

GTIN 4055626257488

Weight per Piece (excluding packing) 33.160 g

Custom tariff number 85363030

Country of origin DE (Germany)

Dimensions

Height 46.7 mm

Width 17.5 mm

Depth 65.7 mm

Horizontal pitch 1 Div.

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude ≤ 6000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 30g (Half-sine / 11 ms / $3x \pm X, \pm Y, \pm Z$)
Vibration (operation) 5g (5 ... 500 Hz / 2.5 h / X, Y, Z)
General
EN type T2 / T3
IEC power supply system TN-S
TT
Number of ports One
Mode of protection L-N
L-PE
N-PE
Mounting type on base element
Color light gray RAL 7035
Housing material PA 6.6-FR 20% GF
PA 6.6-FR
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type Male
Number of positions 2
Surge protection fault message optical
Protective circuit
Nominal voltage UN 120 V AC (TN-S)
120 V AC (TT)
Nominal frequency f_N 50 Hz (60 Hz)
Maximum continuous voltage UC 150 V AC
Residual current IPE $\leq 5 \mu A$
Nominal discharge current $I_n(8/20) \mu s$ 5 kA
Standby power consumption PC ≤ 10.6 mVA (at UREF)
 ≤ 13.5 mVA (at UC)
Reference test voltage UREF 132 V AC
Max. discharge current $I_{max}(8/20) \mu s$ 10 kA
Combination wave UOC 6 kV
Voltage protection level $U_p(L-N) \leq 0.75$ kV (at UOC)
 ≤ 0.95 kV (at I_n)
Voltage protection level $U_p(L-PE) \leq 0.85$ kV
Voltage protection level $U_p(N-P...$

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLT-SEC-T3-120-P-UT/PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.