

INDUSTRIAL COMPONENT DATA

PLT-SEC-T3-24-FM-PT 2907925 PHOENIX CONTACT Type 3 surge protection device

Brand: PHOENIX CONTACT | Manufacturer Part Number: PLT-SEC-T3-24-FM-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PLT-SEC-T3-24-FM-PT
Catalog number	2907925
Category	Surge protection device for terminal equipment
Minimum order	1 Pcs
Document ID	EO-4628AD9424
Generated	2026-08-02

Product Overview

Type 3 surge protection device

Type 3 surge protection, consisting of plug-in protection and base element, with integrated status indicator and remote indication for single-phase power supply networks. Rated voltage: 24VAC/DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Trabtech (TT)**

Additional Product Information

Key Commercial Data

Orderkey 2907925

Packing unit 5 pc

GTIN 4055626257495

Weight per Piece (excluding packing) 77.160 g

Custom tariff number 85363030

Country of origin DE (Germany)

Dimensions

Height 101 mm

Width 17.7 mm

Depth 74.5 mm (incl. DIN rail 7.5 mm)

Horizontal pitch 1 Div.

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude $\leq$ 2000 m (operating voltage remote contact $\leq$ 250 V)

$\leq$ 6000 m (operating voltage remote contact $\leq$ 150 V)

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 30g (Half-sine / 11 ms / $3x \pm X, \pm Y, \pm Z$)

Vibration (operation) 5g (5 ... 500 Hz / 2.5 h / X, Y, Z)

General

EN type T3

IEC power supply system TN-S

Number of ports One

Mode of protection L-N

L-PE

N-PE

Mounting type DIN rail: 35 mm

Color light gray RAL 7035

traffic grey A RAL 7042

Housing material PA 6.6-FR 20% GF

PA 6.6-FR

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type DIN rail module, two-section, divisible

Number of positions 2

Surge protection fault message Optical, remote indicator contact

Protective circuit

Nominal voltage UN 24 V AC (TN-S)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous voltage UC 34 V AC

Rated load current IL 26 A (at 30 °C)

Residual current IPE $\leq$ 5 μ A

Nominal discharge current $I_n(8/20)$ μ s 1 kA

Standby power consumption PC $\leq$ 2.7 mVA (at UREF)

$\leq$ 4.8 mVA (at UC)

Reference test voltage UREF 27 V AC

Combination wave UOC 2 kV

Volta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PLT-SEC-T3-24-FM-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.