

INDUSTRIAL COMPONENT DATA

FMC 0,5/ 3-ST-2,54 C1 1706262 PHOENIX CONTACT Plug component, Nominal current: 6 A, Rated voltage (III/2): 1..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FMC 0,5/ 3-ST-2,54 C1



Manufacturer	PHOENIX CONTACT
MPN / Reference	FMC 0,5/ 3-ST-2,54 C1
Catalog number	1706262
Category	Cable connector
Minimum order	200 Pcs
Document ID	EO-713CB38C97
Generated	2026-08-03

Product Overview

Plug component, Nominal current: 6 A, Rated voltage (III/2): 160 V, Number of positions: 3, Pitch: 2.54 mm, Connection method: Push-in spring connection, Color: black, Contact surface: Gold, Fixed coding of the first position, can be combined with MC(V) 0,5/...-G-2,54...C1 headers

Connector for printed circuit board, nominal section: 0.5 mm², color: black, nominal current: 6 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: FMC 0.5/.. -ST, pitch: 2.54mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON FMC 0.5, locking: without, fixing type: without, packing type: box-packed, first pole fixed coding; can be combined with MC(V) 0.5/...-G-2.54...C1 base housings

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Dimensions

Length 15.4 mm

Height 5.4 mm

Width 8.08 mm

Pitch 2.54 mm

Dimension a 5.08 mm

General

Range of articles FMC 0,5/...-ST

Insulating material group IIIa
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/3) 32 V
Rated voltage (III/2) 160 V
Rated voltage (II/2) 160 V
Connection in acc. with standard EN-VDE
Nominal current I_N 6 A
Nominal cross section 0.5 mm²
Insulating material LCP
Flammability rating according to UL 94 V0
Stripping length 7 mm
Number of positions 3
Connection data
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 0.5 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 0.34 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.25 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 20
ETIM for 1706262 Connectors (EC002638)
Feature Name
Feature Value
Type of connection (EF000064)
Other
Contact type (EF001587)
Bus
Number of poles (EF001391)
3
Number of plug-in contact rows (EF006935)
1
Modular spacing contacts (EF007326)
2.54 mm
Modular spacing connections (EF006827)
2.54 mm
Angle contact/conductor connection (EF007546)
Other
Rated c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FMC 0,5/ 3-ST-2,54 C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.