

INDUSTRIAL COMPONENT DATA

MC 1,5/ 5-ST-3,81-LR 1817071 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC 1,5/ 5-ST-3,81-LR



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC 1,5/ 5-ST-3,81-LR
Catalog number	1817071
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-65B0FB28FC
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: MC 1.5/.. -ST-LR, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping shape: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, lock: Socket lock, fixing type: Lock & Release extractor lever, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1817071

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 191 (C-1-2013)

GTIN 4046356754194

Weight per Piece (excluding packing) 4.320 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 27.5 mm

Width [w] 25.94 mm

Height [h] 13.6 mm

Pitch 3.81 mm

Dimension a 15.24 mm

General

Range of articles MC 1,5/...-ST-LR

Number of positions 5

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Nominal cross section 1.5 mm²

Maximum load current 8 A (with 1.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7 mm

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC 1,5/ 5-ST-3,81-LR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.