

INDUSTRIAL COMPONENT DATA

HSCP-SP 2,5-1UTT-7035 2201781 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: HSCP-SP 2,5-1UTT-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HSCP-SP 2,5-1UTT-7035
Catalog number	2201781
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-528DA2F89C
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal cross-section: 2.5 mm², colour: luminous grey, nominal current: 8 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 2, number of poles: 2, number of connections: 4, article family: HSCP-SP 2.5-..., pitch: 5 mm, connection type: Push-in spring connection, conductor connection/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: HSC 2.5, locking: without, fixing type: without, packaging type: boxed, Normally spring-closed contact color: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2201781

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 35 (NTK-2014)

GTIN 4046356911443

Weight per Piece (excluding packing) 3.640 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 10.9 mm

Width [w] 18.8 mm

Height [h] 21.6 mm

Pitch 5 mm

General

Number of positions 2

Connection method Push-in technology

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 300 V

Rated voltage (II/2) 600 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 A

Nominal cross section 2.5 mm²

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammability rating according to UL 94 V0

Environm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HSCP-SP 2,5-1UTT-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.