


INDUSTRIAL COMPONENT DATA

DFK-IPC 16/ 3-STF-10,16 1703784 PHOENIX CONTACT

Feed-through plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-IPC 16/ 3-STF-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-IPC 16/ 3-STF-10,16
Catalog number	1703784
Category	Cable connector
Minimum order	10 Pcs
Document ID	EO-43B6FF91AD
Generated	2026-08-02

Product Overview

Feed-through plug

Wall pass block, nominal section: 16 mm², color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: DFK-IPC 16/.. -STF, pitch: 10.16 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1703784

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 585 (C-1-2013)

GTIN 4017918994624

Weight per Piece (excluding packing) 38.680 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 56.4 mm

Width [w] 71.56 mm

Height [h] 32.05 mm

Pitch 10.16 mm

Dimension a 20.32 mm

General

Range of articles DFK-IPC 16/..-STF

Number of positions 3

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I_N 76 ANominal cross section 16 mm²

Maximum load current 76 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A6

Stripping length 12 mm

Screw thread M4

Tightening torque, min 1.7 Nm

Tightening torque max 1.8 Nm

Connection dataConductor cross section solid min. 0.75 mm²Conductor cross section solid max. 16 mm²Conductor cross section flexible min. 0.75 mm²Conductor cross section flexible max. 16 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm² Only in connection with CRIMPFOX 16 SConductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²

Conductor cross section....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-IPC 16/ 3-STF-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.