

INDUSTRIAL COMPONENT DATA

DFK-MC 1,5/ 7-GF-3,81 1829390 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-MC 1,5/ 7-GF-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-MC 1,5/ 7-GF-3,81
Catalog number	1829390
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-7AC06BFB9E
Generated	2026-07-27

Product Overview

Feed-through header

Wall pass-through housing, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: DFK-MC 1.5/..-GF, pitch: 3.81 mm, connection type: Solder/flat plug connection, mounting: Direct mounting, pin arrangement: Linear pin arrangement, pin length [P]: 9.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: Screw lock, fixing type: Air clamping (thread), Packaging Type: Boxed Packaging

Feed-through header, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Pin, number of potentials: 7, number of rows: 1, number of positions: 7, number of connections: 7, product range: DFK-MC 1,5/..-GF, pitch: 3.81 mm, connection method: Solder/Slip-on connection, mounting: Direct mounting, pin layout: Linear pinning, solder pin [P]: 9.4 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1,5, Pin connector pattern alignment: Standard, locking: Screw locking mechanism, mounting: Threaded flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type Feed-through header

Product family DFK-MC 1,5/..-GF

Product line COMBICON Connectors S

Type Feed-through header
Number of positions 7
Pitch 3.81 mm
Number of connections 7
Number of rows 1
Number of potentials 7
Mounting flange Threaded flange
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 02
Electrical propertiesNominal current IN 8 A
Nominal voltage UN 160 V
Contact resistance 2.2 mΩ
Rated voltage (III/3) 160 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 320 V
Rated surge voltage (II/2) 2.5 kV
MountingMounting type Direct mounting
Pin layout Linear pinning
Flange
Tightening torque 0.3 Nm
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface contact area (top layer) Tin (5 - 7 μm Sn)
Metal surface contact area (middle layer) Nickel (2 - 3 μm Ni)
Metal surface soldering area (top layer) Tin (5 - 7 μm Sn)
Metal surface soldering area (middle layer) Nickel (2 - 3 μm Ni)
Material data - housing
Color (Housing) green (6021)
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammability rating according to UL 94 V0
Glow wire flammability index GWFI according to EN 60695-2-12 850
Glow wire ignition temperature GWIT according to EN 60695-2-12 850

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-MC 1,5/ 7-GF-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.