

INDUSTRIAL COMPONENT DATA

DFK-MSTB 2,5/ 5-GF-5,08 0710206 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-MSTB 2,5/ 5-GF-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-MSTB 2,5/ 5-GF-5,08
Catalog number	0710206
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-63311E16BD
Generated	2026-07-28

Product Overview

Printed-circuit board connector

Wall pass-through housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: DFK-MSTB 2.5/.. -GF, pitch: 5.08 mm, connection type: Solder/flat plug connection, mounting: Direct mounting, pin arrangement: Linear pin arrangement, pin length [P]: 9.3 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: Screw lock, fixing type: Air clamping (thread), Packaging Type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 0710206

Packing unit 50 pc

Catalog page Page 353 (C-1-2013)

GTIN 4017918005238

Weight per Piece (excluding packing) 5.870 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 17.5 mm

Width [w] 45.72 mm

Height [h] 29.5 mm

Pitch 5.08 mm

Dimension a 20.32 mm

Dimensions of slip-on connection 2,8 x 0,8 mm

General

Range of articles DFK-MSTB 2,5/..-GF

Number of positions 5

Connection method Solder/Slip-on connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V2

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Max. current slip-on connection

Dimensions of slip-on connection 2,8 x 0,8 mm

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V2

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Download..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-MSTB 2,5/ 5-GF-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.