

INDUSTRIAL COMPONENT DATA

DFK-MSTB 2,5/ 8-G-5,08 0707057 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK-MSTB 2,5/ 8-G-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK-MSTB 2,5/ 8-G-5,08
Catalog number	0707057
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-D5CC875163
Generated	2026-07-28

Product Overview

Feed-through header

Wall pass-through housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: DFK-MSTB 2.5/.. -G, pitch: 5.08 mm, connection type: Solder/flat plug connection, mounting: Direct mounting, pin arrangement: Linear pin arrangement, pin length [P]: 9.3 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: Packaged in a box, the accessory with the 5030172 code is only usable in combination with MSTB 2.5/... ST-5.08 and MSTBT 2.5/... ST-5.08.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 0707057

Packing unit 50 pc

Catalog page Page 352 (C-1-2013)

GTIN 4017918003838

Weight per Piece (excluding packing) 7.810 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 17.5 mm

Width [w] 60.96 mm

Height [h] 29.5 mm

Pitch 5.08 mm

Dimension a 35.56 mm

Dimensions of slip-on connection 2,8 x 0,8 mm

General

Range of articles DFK-MSTB 2,5/..-G

Number of positions 8

Connection method Solder/Slip-on connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V2

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Max. current slip-on connection 8 A

Dimensions of slip-on connection 2,8 x 0,8 mm

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK-MSTB 2,5/ 8-G-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.