


## INDUSTRIAL COMPONENT DATA

# FK-MCP 1,5/12-ST-3,5 1940004 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/12-ST-3,5



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | PHOENIX CONTACT      |
| MPN / Reference | FK-MCP 1,5/12-ST-3,5 |
| Catalog number  | 1940004              |
| Category        | Cable connector      |
| Minimum order   | 50 Pcs               |
| Document ID     | EO-ACE877B0CC        |
| Generated       | 2026-07-29           |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm<sup>2</sup>, color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: FK-MCP 1.5/..-ST, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 1.5 mm<sup>2</sup>, color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 12, number of rows: 1, number of positions: 12, number of connections: 12, product range: FK-MCP 1,5/..-ST, pitch: 3.5 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: without, mounting: without, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

### Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family FK-MCP 1,5/..-ST

Product line COMBICON Connectors S

Type Standard

Number of positions 12

Pitch 3.5 mm  
Number of connections 12  
Number of rows 1  
Number of potentials 12  
Mounting flange without  
Data management status  
Article revision 03  
Electrical propertiesNominal current  $I_N$  8 A  
Nominal voltage  $U_N$  160 V  
Contact resistance 2 m $\Omega$ ?  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 160 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 320 V  
Rated surge voltage (II/2) 2.5 kV  
Connection dataConnection technology  
Type Standard  
Connector system COMBICON MC 1,5  
Nominal cross section 1.5 mm<sup>2</sup>  
Contact connection type Socket  
Interlock  
Locking type without  
Mounting flange without  
Conductor connection  
Connection method Push-in spring connection  
Conductor/PCB connection direction 0 °  
Conductor cross section rigid 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section flexible 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section AWG 26 ... 16  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>  
Cylindrical gauge a x b / diameter 2.4 mm x 1.5 mm / -  
Stripping length 9 mm  
Specifications for ferrules without insulating collar  
recommended crimping tool 1212034 CRIMPFOX 6  
ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm<sup>2</sup>; Length: 7 mm  
Cross s...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/12-ST-3,5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.