


INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/12-STF-3,81 1851339 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/12-STF-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/12-STF-3,81
Catalog number	1851339
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-609D9AA198
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: FK-MCP 1,5/..-STF, pitch: 3.81 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: Screw lock, fixing type: Air clamp (screw), packaging type: boxed

PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 12, number of rows: 1, number of positions: 12, number of connections: 12, product range: FK-MCP 1,5/..-STF, pitch: 3.81 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0°, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family FK-MCP 1,5/..-STF

Product line COMBICON Connectors S

Type Standard

Number of positions 12

Pitch 3.81 mm
Number of connections 12
Number of rows 1
Number of potentials 12
Mounting flange Screw flange
Data management status
Article revision 09
Electrical propertiesNominal current I_N 8 A
Nominal voltage U_N 160 V
Contact resistance 1.4 m Ω
Rated voltage (III/3) 160 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 320 V
Rated surge voltage (II/2) 2.5 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON MC 1,5
Nominal cross section 1.5 mm²
Contact connection type Socket
Interlock
Locking type Screw locking mechanism
Mounting flange Screw flange
Tightening torque 0.3 Nm
Conductor connection
Connection method Push-in spring connection
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG 26 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.75 mm²
Cylindrical gauge a x b / diameter 2.4 mm x 1.5 mm / -
Stripping length 9 mm
Specifications for ferrules without insulating collar
recommended crimping tool 1212034 CRIMPFOX 6
ferrules without insulating collar, according to D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/12-STF-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.