


INDUSTRIAL COMPONENT DATA

FKC 2,5/ 8-ST-5,08-LR 1792575 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/ 8-ST-5,08-LR



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/ 8-ST-5,08-LR
Catalog number	1792575
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-69500DD50A
Generated	2026-07-28

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, family of articles: FKC 2.5/.. -ST-LR, pitch: 5.08 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Snap lock, fixing type: Lock & Release puller lever, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1792575

Packing unit 50 pc

Catalog page Page 275 (C-1-2013)

GTIN 4046356615587

Weight per Piece (excluding packing) 15.350 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 33.52 mm

Width [w] 50.16 mm

Height [h] 15 mm

Pitch 5.08 mm

Dimension a 35.56 mm

General

Range of articles FKC 2,5/..-ST-LR

Number of positions 8

Connection method Push-in spring connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A2

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, stranded, TWIN....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/ 8-ST-5,08-LR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.