


INDUSTRIAL COMPONENT DATA

FKCVW 2,5/10-STF-5,08 1873883 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKCVW 2,5/10-STF-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKCVW 2,5/10-STF-5,08
Catalog number	1873883
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-542D9771CA
Generated	2026-07-29

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, family of articles: FKCVW 2.5/.. -STF, pitch: 5.08 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: -90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

PCB connector, nominal cross-section: 2.5 mm², colour: green, rated current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Sn, contact connection type: Female, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, product series: FKCVW 2.5/.. -STF, pitch: 5.08 mm, connection type: Push-in spring connection, conductor/board connection direction: -90 °, locking hook: - Locking hook, plug system: COMBICON MSTB 2.5, locking: Screw locking, fixing type: Screw flange, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1873883

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 281 (C-1-2013)

GTIN 4017918143275

Weight per Piece (excluding packing) 18.070 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 26.6 mm

Width [w] 60.9 mm

Height [h] 19.2 mm

Pitch 5.08 mm

Dimension a 45.72 mm

General

Range of articles FKCVW 2,5/...-STF

Number of positions 10

Connection method Push-in spring connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A2

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AW...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKCVW 2,5/10-STF-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.