


INDUSTRIAL COMPONENT DATA

FRONT-MC 1,5/ 4-STF-3,81 1850877 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FRONT-MC 1,5/ 4-STF-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	FRONT-MC 1,5/ 4-STF-3,81
Catalog number	1850877
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-D3F1E3CC53
Generated	2026-07-28

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: FRONT-MC 1.5/.. -STF, pitch: 3.81 mm, connection type: Front screw connection, screw clamping shape: L Longitudinal slot, driver/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, locking: Screw lock, fixing type: Air clamping (screw), packaging type: boxed

PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: FRONT-MC 1,5/..-STF, pitch: 3.81 mm, connection method: Front screw connection, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family FRONT-MC 1,5/..-STF

Product line COMBICON Connectors S

Type Standard

Number of positions 4

Pitch 3.81 mm
Number of connections 4
Number of rows 1
Number of potentials 4
Mounting flange Screw flange
Data management status
Article revision 17
Electrical propertiesNominal current IN 8 A
Nominal voltage UN 160 V
Contact resistance 1.6 mΩ
Rated voltage (III/3) 160 V
Rated surge voltage (III/3) 2.5 kV
Rated voltage (III/2) 160 V
Rated surge voltage (III/2) 2.5 kV
Rated voltage (II/2) 320 V
Rated surge voltage (II/2) 2.5 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON MC 1,5
Nominal cross section 1.5 mm²
Contact connection type Socket
Interlock
Locking type Screw locking mechanism
Mounting flange Screw flange
Tightening torque 0.3 Nm
Conductor connection
Connection method Front screw connection
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.14 mm² ... 1.5 mm²
Conductor cross section flexible 0.14 mm² ... 1.5 mm²
Conductor cross section AWG 28 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.5 mm²
2 conductors with same cross section, solid 0.14 mm² ... 0.5 mm²
2 conductors with same cross section, flexible 0.14 mm² ... 0.75 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FRONT-MC 1,5/ 4-STF-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.