

INDUSTRIAL COMPONENT DATA

GFKC 2,5/ 2-ST-7,62 1939633 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: GFKC 2,5/ 2-ST-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	GFKC 2,5/ 2-ST-7,62
Catalog number	1939633
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-137E3555D4
Generated	2026-07-31

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: GFKC 2.5/.. -ST, pitch: 7.62 mm, connection type: Push-in spring connection, conductor connection direction/printed circuit board: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1939633

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 340 (C-1-2013)

GTIN 4017918877699

Weight per Piece (excluding packing) 3.900 g

Custom tariff number 85366990

Country of origin DE (Germany)

Item properties

Brief article description Printed-circuit board connector

Plug-in system CLASSIC COMBICON

Type of contact Female connector

Range of articles GFKC 2,5/..-ST

Pitch 7.62 mm

Number of positions 2

Connection method Push-in spring connection

Locking without

Number of levels 1

Number of connections 2

Number of potentials 2

Electrical parameters

Rated current 12 A

Rated insulation voltage (III/2) 630 V

Rated surge voltage (III/2) 6 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG / kcmil 24 ... 12

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1.5 mm²

Cylindrical gauge a x b / diameter 2.8 mm x 2.0 mm / 2.3 mm

Stripping length 10 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Material data - housing

Insulating material PA

Insulating material group I

CTI according t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GFKC 2,5/ 2-ST-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.