

INDUSTRIAL COMPONENT DATA

GFKC 2,5/ 3-STF-7,62 1939756 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: GFKC 2,5/ 3-STF-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	GFKC 2,5/ 3-STF-7,62
Catalog number	1939756
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-659843E116
Generated	2026-07-29

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: GFKC 2.5/.. -STF, pitch: 7.62 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1939756

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 341 (C-1-2013)

GTIN 4017918877774

Weight per Piece (excluding packing) 6.810 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 25.6 mm

Width [w] 32.46 mm

Height [h] 15 mm

Pitch 7.62 mm

Dimension a 15.24 mm

General

Range of articles GFKC 2,5/...-STF

Number of positions 3

Connection method Push-in spring connection

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 400 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A (with a 2.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A2

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GFKC 2,5/ 3-STF-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.