

INDUSTRIAL COMPONENT DATA

GMSTB 2,5/ 5-STF-7,62 EX 1795802 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5/ 5-STF-7,62 EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTB 2,5/ 5-STF-7,62 EX
Catalog number	1795802
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-B240A53AB6
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: GMSTB 2.5/.. -STF-EX, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON MSTB 2.5 EX, locking: Screw locking, fixing type: Air clamping (screw), packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1795802

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 379 (C-1-2013)

GTIN 4046356635677

Weight per Piece (excluding packing) 10.950 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 18.2 mm

Width [w] 48.49 mm

Height [h] 15 mm

Pitch 7.62 mm

Dimension a 30.48 mm

General

Range of articles GMSTB 2,5/..-STF-EX

Number of positions 5

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 400 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 ANominal cross section 2.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with pla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5/ 5-STF-7,62 EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.