


INDUSTRIAL COMPONENT DATA

GMSTB 2,5 HCV/ 2-ST-7,62 1714278 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5 HCV/ 2-ST-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	GMSTB 2,5 HCV/ 2-ST-7,62
Catalog number	1714278
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-B75E7A275C
Generated	2026-07-28

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 16 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: GMSTB 2.5 HCV/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5 HC, locking: without, fixing type: without, packaging type: packed in box

Conductive plate connector, nominal cross-section: 2.5 mm², colour: green, nominal current: 16 A, reference voltage (III/2): 1000 V, contact surface: Sn, contact type: Female connector, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, item range: GMSTB 2.5 HCV/.. -ST, pitch: 7.62 mm, connection type: Screwed connection with ring, screw driving surface: L Longitudinal slot, conductor/PCB plugging direction: 0°, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2.5 HC, locking: without, fastening type: without, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1714278

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 502 (C-1-2013)

GTIN 4046356094665

Weight per Piece (excluding packing) 3.900 g

Custom tariff number 85366990

Country of origin DE (Germany)

Item properties

Brief article description Printed-circuit board connector

Plug-in system POWER COMBICON 2,5

Type of contact Female connector

Range of articles GMSTB 2,5 HCV/..-ST

Pitch 7.62 mm

Number of positions 2

Connection method Screw connection with tension sleeve

Drive form screw head Slotted (L)

Screw thread M3

Locking without

Number of levels 1

Number of connections 2

Number of potentials 2

Electrical parameters

Rated current 16 A

Rated insulation voltage (III/2) 1000 V

Rated surge voltage (III/2) 8 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG / kcmil 24 ... 12

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 1 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm² ... 1 mm²

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm² ... 1 mm²

Cylindrical gauge a x b / diameter 2.8 mm x 2.4 mm / 2.5....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5 HCV/ 2-ST-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.