

INDUSTRIAL COMPONENT DATA

HBUS 53,6-16P-1S BK 2896458 PHOENIX CONTACT DIN rail bus connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: HBUS 53,6-16P-1S BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	HBUS 53,6-16P-1S BK
Catalog number	2896458
Category	Cable connector
Minimum order	10 Pcs
Document ID	EO-2D1A8F7F2D
Generated	2026-07-29

Product Overview

DIN rail bus connectors

Rail bus connectors, colour: black, rated current: 3 A (max. total current 25 A), rated voltage (III/2): 30 V, number of poles: 16, pitch: 2.54 mm, mounting: Rail mounting, locking: without

DIN rail connector, color: black, nominal current: 3 A (Total current of 25 A max.), rated voltage (III/2): 30 V, number of positions: 16, product range: BC 53,6.., pitch: 2.54 mm, mounting: DIN rail mounting, locking: without

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type DIN rail connector

Product family BC 53,6..

Number of positions 16

Pitch 2.54 mm

Data management status

Article revision 03

Electrical propertiesNominal current IN 3 A (Total current of 25 A max.)

Contact resistance 23.9 mΩ

Rated voltage (III/3) 30 V

Rated surge voltage (III/3) 0.8 kV

Rated voltage (III/2) 30 V

Rated surge voltage (III/2) 0.8 kV
Rated voltage (II/2) 100 V
Rated surge voltage (II/2) 0.8 kV
Connection dataMaximum load current 3 A (maximum total current 23 A)
Material specificationsMaterial data - contact
Contact material Cu alloy
Surface characteristics Completely gold-plated
Material data - housing
Color (Housing) black (9005)
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammability rating according to UL 94 V0
material specifications - connector
Color () ()
DimensionsPitch 2.54 mm
Width [w] 53.6 mm
Height [h] 13.6 mm
Length [l] 37.1 mm
MountingMounting type DIN rail mounting
Mechanical testsVisual inspection
Specification IEC 60512-1-1:2002-02
Result Test passed
Dimension check
Specification IEC 60512-1-2:2002-02
Result Test passed
Environmental and real-life conditionsVibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 20 m/s²
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis (pos. and neg.)
Durability test
Specification IEC 60512-9-1:2010-03
Impulse withstand vo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HBUS 53,6-16P-1S BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.