

INDUSTRIAL COMPONENT DATA

IPC 16/ 7-ST-10,16 1969425 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 16/ 7-ST-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	IPC 16/ 7-ST-10,16
Catalog number	1969425
Category	Cable connector
Minimum order	25 Pcs
Document ID	EO-FE3C440361
Generated	2026-07-28

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 16 mm², color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: IPC 16/.. -ST, pitch: 10.16 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 16, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1969425

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 558 (C-1-2013)

GTIN 4017918943677

Weight per Piece (excluding packing) 64.530 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 44.1 mm

Width [w] 74.16 mm

Height [h] 27.8 mm

Pitch 10.16 mm

Dimension a 60.96 mm

General

Range of articles IPC 16/...-ST

Number of positions 7

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I_N 76 ANominal cross section 16 mm²

Maximum load current 76 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A6

Stripping length 12 mm

Screw thread M4

Tightening torque, min 1.7 Nm

Tightening torque max 1.8 Nm

Connection dataConductor cross section solid min. 0.75 mm²Conductor cross section solid max. 16 mm²Conductor cross section flexible min. 0.75 mm²Conductor cross section flexible max. 16 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm² Only in connection with CRIMPFOX 16 S

Conductor cross section flexible, with ferrule with plastic sleeve min. 0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 16/ 7-ST-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.