

INDUSTRIAL COMPONENT DATA

IPC 35 HC/ 6-STF-15,00 1784839 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 35 HC/ 6-STF-15,00



Manufacturer	PHOENIX CONTACT
MPN / Reference	IPC 35 HC/ 6-STF-15,00
Catalog number	1784839
Category	Cable connector
Minimum order	10 Pcs
Document ID	EO-F358F7BBDD
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 35 mm², color: green, nominal current: 125 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, article family: IPC 35 HC/.. -STF, pitch: 15 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 35, locking: Screw locking, fixing type: Air clamping (screw), packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1784839

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 588 (C-1-2013)

GTIN 4046356561143

Weight per Piece (excluding packing) 195.200 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 58 mm

Width [w] 91.3 mm

Height [h] 40 mm

Pitch 15 mm

Dimension a 75 mm

General

Range of articles IPC 35 HC/..-STF

Number of positions 6

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 8 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 125 A

Nominal cross section 35 mm²

Maximum load current 125 A

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 20 mm

Screw thread M5

Tightening torque, min 2.5 Nm

Tightening torque max 4.5 Nm

Note Tightening torque ≤ 25 mm² is 2.5 Nm, > 25 mm² is 4.5 Nm

Connection data

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 35 mm²

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 35 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 1 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 1.5 mm²

Conduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 35 HC/ 6-STF-15,00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.