


INDUSTRIAL COMPONENT DATA

IPC 5/ 9-STF-7,62 1709225 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 5/ 9-STF-7,62



Manufacturer	PHOENIX CONTACT
MPN / Reference	IPC 5/ 9-STF-7,62
Catalog number	1709225
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-AF969F7F28
Generated	2026-08-01

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Male, number of potentials: 9, number of rows: 1, number of poles: 9, number of connections: 9, article family: IPC 5/.. -STF, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: Z1L Pozidriv with longitudinal groove, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 5, locking: Screw lock, fixing type: Air clamping (screw), packaging type: Boxed Packaging

PCB connector, nominal cross-section: 6 mm², color: green, rated current: 41 A, rated voltage (III/2): 1000 V, contact surface: Sn, contact type: pin, number of potentials: 9, number of rows: 1, number of poles: 9, number of connectors: 9, article family: IPC 5/.. -STF, Pitch: 7.62 mm, Connection type: Screw connection with pull sleeve, Screw attack form: Z1L Pozidriv with longitudinal slot, Connection direction conductor/board: 0 °, Locking hook: - without locking hook, Plug-in system: COMBICON PC 5, Locking: Screw lock, Mounting type: Screw flange, Packaging type: packed in a cardboard box

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1709225

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 527 (C-1-2013)

GTIN 4046356075763

Weight per Piece (excluding packing) 42.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 36.55 mm

Width [w] 68.58 mm

Height [h] 22.9 mm

Pitch 7.62 mm

Dimension a 60.96 mm

General

Range of articles IPC 5/...-STF

Number of positions 9

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 41 A

Nominal cross section 6 mm²

Maximum load current 41 A

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 10 mm

Screw thread M3

Tightening torque, min 0.7 Nm

Tightening torque max 0.8 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 10 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 6 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic slee...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 5/ 9-STF-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.