


## INDUSTRIAL COMPONENT DATA

# MCC 1/12-STZ-3,81 1852273 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCC 1/12-STZ-3,81



|                 |                   |
|-----------------|-------------------|
| Manufacturer    | PHOENIX CONTACT   |
| MPN / Reference | MCC 1/12-STZ-3,81 |
| Catalog number  | 1852273           |
| Category        | Cable connector   |
| Minimum order   | 50 Pcs            |
| Document ID     | EO-7FFCD6C318     |
| Generated       | 2026-07-31        |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1 mm<sup>2</sup>, color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact connection type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: MCC 1/.. -STZ, pitch: 3.81 mm, connection type: Crimp connection, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: box-packed, corresponding crimped female contacts, with indications regarding the current [A] and the range of conductor cross-sections [mm<sup>2</sup>]: 5A/MCC-MT 0.2-0.35 (1859988). 8A/MCC-MT 0.5-1.0 (1859991)

PCB connector, nominal cross-section: 1 mm<sup>2</sup>, colour: green, rated current: 8 A, dimensioning voltage (III/2): 160 V, contact connection type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, product series: MCC 1/.. -STZ, pitch: 3.81 mm, connection type: Crimp connection, conductor/board connection direction: 0 °, plug system: COMBICON MC 1.5, locking: none, fastening type: none, packaging type: packed in the carton, The respective crimp contacts with data regarding current [A] and cross-sectional area of the conductor [mm<sup>2</sup>]: 5A/MCC-MT 0.2-0.35 (1859988); 8A/MCC-MT 0.5-1.0 (1859991)

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

### Additional Product Information

Key Commercial Data

Orderkey 1852273

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 206 (C-1-2013)

GTIN 4017918143831

Weight per Piece (excluding packing) 3.560 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [ l ] 23.1 mm

Width [ w ] 46.51 mm

Height [ h ] 8.7 mm

Pitch 3.81 mm

Dimension a 41.91 mm

General

Range of articles MCC 1/..-STZ

Number of positions 12

Connection method Crimp connection

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1 mm<sup>2</sup>

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Connection data

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 1 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max. 18

Minimum AWG according to UL/CUL 20

Maximum AWG according to UL/CUL 18

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCC 1/12-STZ-3,81 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.