

INDUSTRIAL COMPONENT DATA

MCC 1/ 4-STZ-3,81 1852192 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCC 1/ 4-STZ-3,81



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCC 1/ 4-STZ-3,81
Catalog number	1852192
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-1814FF78ED
Generated	2026-07-29

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1 mm², color: green, rated current: 8 A, sizing voltage (III/2): 160 V, contact type: Connection female, Number of potentials: 4, Number of rows: 1, Number of row poles: 4, number of connections: 4, article family: MCC 1/.. -STZ, pitch: 3.81 mm, connection type: Set connection, connection direction conductor/printed circuit board: 0 °, Stecksystem: MINI COMBICON, Locking: without, type of packaging: boxed, corresponding set female contacts, with indications regarding current [A] and range of conductor sections [mm²]: 5A/MCC-MT 0.2-0.35 (1859988); 8A/MCC-MT 0.5-1.0 (1859991)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1852192

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 206 (C-1-2013)

GTIN 4017918125837

Weight per Piece (excluding packing) 1.090 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 23.1 mm

Width [w] 16.03 mm

Height [h] 8.7 mm

Pitch 3.81 mm

Dimension a 11.43 mm

General

Range of articles MCC 1/...-STZ

Number of positions 4

Connection method Crimp connection

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current I_N 8 ANominal cross section 1 mm²

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Connection dataConductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 1 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 18

Minimum AWG according to UL/CUL 20

Maximum AWG according to UL/CUL 18

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

ClassificationseCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440309eCl@ss 8.027440309eCl@ss 9...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCC 1/ 4-STZ-3,81 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.