

**INDUSTRIAL COMPONENT DATA**

# MCVR 1,5/16-ST-3,81 1827266 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCVR 1,5/16-ST-3,81



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | MCVR 1,5/16-ST-3,81 |
| Catalog number  | 1827266             |
| Category        | Cable connector     |
| Minimum order   | 50 Pcs              |
| Document ID     | EO-9997FA2D1B       |
| Generated       | 2026-08-02          |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 16, number of rows: 1, number of poles: 16, number of connections: 16, family of articles: MCVR 1.5/.. -ST, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, connection direction conductor/printed circuit board: 90 °, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

### Additional Product Information

Key Commercial Data

Orderkey 1827266

Packing unit 50 pc

Catalog page Page 192 (C-1-2013)

GTIN 4017918114381

Weight per Piece (excluding packing) 12.330 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [ l ] 10.4 mm

Width [ w ] 61.75 mm

Height [ h ] 19.1 mm

Pitch 3.81 mm

Dimension a 57.15 mm

General

Range of articles MCVR 1,5/...-ST

Number of positions 16

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 160 V

Rated voltage (II/2) 320 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 8 A

Nominal cross section 1.5 mm<sup>2</sup>

Maximum load current 8 A (with 1.5 mm<sup>2</sup> conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A1

Stripping length 7 mm

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.14 mm<sup>2</sup>

Conductor cross section solid max. 1.5 mm<sup>2</sup>

Conductor cross section flexible min. 0.14 mm<sup>2</sup>

Conductor cross section flexible max. 1.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCVR 1,5/16-ST-3,81 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.