

## INDUSTRIAL COMPONENT DATA

# MSTB 2,5/ 3-STF-5,08 EX 1795569 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/ 3-STF-5,08 EX



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | PHOENIX CONTACT         |
| MPN / Reference | MSTB 2,5/ 3-STF-5,08 EX |
| Catalog number  | 1795569                 |
| Category        | Cable connector         |
| Minimum order   | 50 Pcs                  |
| Document ID     | EO-2B96E82E71           |
| Generated       | 2026-08-02              |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MSTB 2.5/.. -STF-EX, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal groove, connection direction conductor/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON MSTB 2.5 EX, locking: Screw locking, fixing type: Air clamping (screw), packaging type: Boxed Packaging

PCB connector, nominal cross-section: 2.5 mm<sup>2</sup>, color: green, rated current: 12 A, contact surface: Sn, contact type: female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connectors: 3, article family: MSTB 2.5/.. -STF-EX, pitch: 5.08 mm, connection type: screw connection with pull sleeve, screw attack shape: L longitudinal slot, connection direction conductor/board: 0 °, locking hook: - without locking hook, plug-in system: COMBICON MSTB 2.5 EX, locking: screw lock, mounting type: screw flange, packaging type: packed in carton

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Key Commercial Data

Orderkey 1795569

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 369 (C-1-2013)

GTIN 4046356635769

Weight per Piece (excluding packing) 6.300 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [ l ] 18.3 mm

Width [ w ] 25.25 mm

Height [ h ] 15 mm

Pitch 5.08 mm

Dimension a 10.16 mm

General

Range of articles MSTB 2,5/...-STF-EX

Number of positions 3

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm<sup>2</sup>

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 2.5 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm<sup>2</sup>

Cond...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/ 3-STF-5,08 EX with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.