

INDUSTRIAL COMPONENT DATA

MSTB 2,5/ 6-STF-5,08 EX 1795598 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/ 6-STF-5,08 EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTB 2,5/ 6-STF-5,08 EX
Catalog number	1795598
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-D68ECFDA86
Generated	2026-07-29

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, contact surface: Tin, contact type: Female, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: MSTB 2.5/..-STF-EX, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal groove, connection direction conductor/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON MSTB 2.5 EX, locking: Screw locking, fixing type: Air clamping (screw), packaging type: Boxed Packaging

PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, contact surface: Sn, contact connection type: Socket, number of potentials: 6, number of rows: 1, number of positions: 6, number of connections: 6, product range: MSTB 2,5/..-STF-EX, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5 EX, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family MSTB 2,5/..-STF-EX

Product line COMBICON Connectors M

Type Standard

Number of positions 6

Pitch 5.08 mm

Number of connections 6

Number of rows 1

Number of potentials 6

Mounting flange Screw flange

Data management status

Article revision 07

Electrical propertiesNominal current IN 12 A

Nominal voltage UN 176 V

Rated current / conductor cross section 12 A/2.5 mm²

Ex dataEx approval

Identification 0344? II 2GD / Ex eb IIC Gb

EU-type examination certificate KEMA 10ATEX0196 U

IECEX certificate IECEX KEM 10.0093U

Connection dataConnection technology

Type Standard

Connector system COMBICON MSTB 2,5 EX

Nominal cross section 2.5 mm²

Contact connection type Socket

Interlock

Locking type Screw locking mechanism

Mounting flange Screw flange

Tightening torque 0.3 Nm

Conductor connection

Connection method Screw connection with tension sleeve

Conductor/PCB connection direction 0 °

Conductor cross section rigid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 1 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/ 6-STF-5,08 EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.