

INDUSTRIAL COMPONENT DATA

MSTBT 2,5/ 2-ST KMGY 1920545 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBT 2,5/ 2-ST KMGY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBT 2,5/ 2-ST KMGY
Catalog number	1920545
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-A9C6F9E14A
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: luminous gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: MSTBT 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, pin arrangement: Linear pin arrangement, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: Boxed Packaging

PCB connector, nominal cross-section: 2.5 mm², colour: light grey, rated current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Sn, contact connection type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, product series: MSTBT 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with cage, screw attachment form: L Longitudinal slot, conductor/board connection direction: 0 °, pin layout: Linear pinning, locking hook: - Locking hook, plug system: COMBICON MSTB 2.5, locking: none, fixing type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1920545

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 627 (CC-2011)

GTIN 4017918207953

Weight per Piece (excluding packing) 3.360 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 18.1 mm

Width [w] 10 mm

Height [h] 15 mm

Pitch 5 mm

Dimension a 5 mm

General

Range of articles MSTBT 2,5/..-ST

Number of positions 2

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A (with a 2.5 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V2

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBT 2,5/ 2-ST KMGY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.