

INDUSTRIAL COMPONENT DATA

MVSTBR 2,5/11-STF-5,08 EX 1809762 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBR 2,5/11-STF-5,08 EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBR 2,5/11-STF-5,08 EX
Catalog number	1809762
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-2F9B9A6E38
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, rated current: 12 A, surface contacts: Tin, contact type: Connecting female, Number of potentials: 11, Number of rows: 1, Number of poles per row: 11, number of connections: 11, article family: MVSTBR 2,5/.. -STF-EX, pitch: 5.08 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 90 °, Stecksystm: CLASSIC COMBICON (EX), Lock: Screw lock, packaging type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1809762

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 369 (C-1-2013)

GTIN 4046356705165

Weight per Piece (excluding packing) 25.550 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 12.6 mm

Width [w] 66.04 mm

Height [h] 26 mm

Pitch 5.08 mm

Dimension a 50.8 mm

General

Range of articles MVSTBR 2,5/...-STF-EX

Number of positions 11

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with pla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBR 2,5/11-STF-5,08 EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.