

INDUSTRIAL COMPONENT DATA

MVSTBR 2,5 HC/ 3-STF-5,08 1912634 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBR 2,5 HC/ 3-STF-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBR 2,5 HC/ 3-STF-5,08
Catalog number	1912634
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-0319417A29
Generated	2026-08-03

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 16 A (see derating curve), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MVSTBR 2.5 HC/.. -STF, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal groove, connection direction conductor/printed circuit board: 90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5 HC, locking: Screw locking, fixing type: Air clamping (screw), packaging type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1912634

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 493 (C-1-2013)

GTIN 4017918192396

Weight per Piece (excluding packing) 7.420 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 12.6 mm

Width [w] 25.4 mm

Height [h] 26 mm

Pitch 5.08 mm

Dimension a 10.16 mm

General

Range of articles MVSTBR 2,5 HC/..-STF

Number of positions 3

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 16 A (see derating curve)Nominal cross section 2.5 mm²

Maximum load current 16 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBR 2,5 HC/ 3-STF-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.