


INDUSTRIAL COMPONENT DATA

MVSTBR 2,5 HC/ 5-ST-5,08 1912430 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBR 2,5 HC/ 5-ST-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBR 2,5 HC/ 5-ST-5,08
Catalog number	1912430
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-BC6FE3EABD
Generated	2026-07-27

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 16 A (see derating curve), nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: MVSTBR 2.5 HC/..-ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5 HC, locking: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 16 A (see derating curve), rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Socket, number of potentials: 5, number of rows: 1, number of positions: 5, number of connections: 5, product range: MVSTBR 2,5 HC/..-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 90 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5 HC, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family MVSTBR 2,5 HC/..-ST

Product line COMBICON Connectors M

Type Standard

Number of positions 5

Pitch 5.08 mm

Number of connections 5

Number of rows 1

Number of potentials 5

Mounting flange without

Data management status

Article revision 01

Electrical propertiesNominal current I_N 16 A (see derating curve)

Nominal voltage U_N 320 V

Contact resistance 1 m Ω

Rated voltage (III/3) 320 V

Rated surge voltage (III/3) 4 kV

Rated voltage (III/2) 320 V

Rated surge voltage (III/2) 4 kV

Rated voltage (II/2) 630 V

Rated surge voltage (II/2) 4 kV

Connection dataConnection technology

Type Standard

Connector system COMBICON MSTB 2,5 HC

Nominal cross section 2.5 mm²

Contact connection type Socket

Interlock

Locking type without

Mounting flange without

Conductor connection

Connection method Screw connection with tension sleeve

Conductor/PCB connection direction 90 °

Conductor cross section rigid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.2 mm² ... 1 mm²

2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²

2 conductors with....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBR 2,5 HC/ 5-ST-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.