

INDUSTRIAL COMPONENT DATA

MVSTBU 2,5/13-GFB-5,08 1788457 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBU 2,5/13-GFB-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBU 2,5/13-GFB-5,08
Catalog number	1788457
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-39C37EBE67
Generated	2026-07-29

Product Overview

Printed-circuit board connector

Direct plug-in block, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 13, number of rows: 1, number of poles: 13, number of connections: 13, family of articles: MVSTBU 2.5/.. -GFB, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Direct mounting, conductor/printed circuit board connection direction: 0 °, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, locking: Screw lock, fixing type: Air clamping (thread), Packaging Type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1788457

Packing unit 50 pc

Note Made to Order (non-returnable)

Catalog page Page 357 (C-1-2013)

GTIN 4017918043513

Weight per Piece (excluding packing) 36.280 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 20.5 mm

Width [w] 77.36 mm

Height [h] 17.3 mm

Pitch 5.08 mm

Dimension a 60.96 mm

General

Range of articles MVSTBU 2,5/..-GFB

Number of positions 13

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 ANominal cross section 2.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Internal cylindrical gage A3

Stripping length 7 mm

Screw thread M3

Tightening torque, min 0.5 Nm

Tightening torque max 0.6 Nm

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with pla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBU 2,5/13-GFB-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.