


## INDUSTRIAL COMPONENT DATA

# MVSTBW 2,5/11-ST-5,08 1792841 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBW 2,5/11-ST-5,08



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | PHOENIX CONTACT       |
| MPN / Reference | MVSTBW 2,5/11-ST-5,08 |
| Catalog number  | 1792841               |
| Category        | Cable connector       |
| Minimum order   | 50 Pcs                |
| Document ID     | EO-CEF3D70644         |
| Generated       | 2026-08-02            |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 11, number of rows: 1, number of poles: 11, number of connections: 11, family of articles: MVSTBW 2.5/..-ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal groove, conductor connection direction/printed circuit board: -90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 2.5 mm<sup>2</sup>, color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Socket, number of potentials: 11, number of rows: 1, number of positions: 11, number of connections: 11, product range: MVSTBW 2,5/..-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: -90 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

### Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family MVSTBW 2,5/..-ST

Product line COMBICON Connectors M

Type Standard

Number of positions 11  
Pitch 5.08 mm  
Number of connections 11  
Number of rows 1  
Number of potentials 11  
Mounting flange without  
Data management status  
Article revision 02  
Electrical propertiesNominal current IN 12 A  
Nominal voltage UN 320 V  
Contact resistance 2.6 mΩ  
Rated voltage (III/3) 250 V  
Rated surge voltage (III/3) 4 kV  
Rated voltage (III/2) 320 V  
Rated surge voltage (III/2) 4 kV  
Rated voltage (II/2) 630 V  
Rated surge voltage (II/2) 4 kV  
Connection dataConnection technology  
Connector system COMBICON MSTB 2,5  
Nominal cross section 2.5 mm²  
Contact connection type Socket  
Interlock  
Locking type without  
Mounting flange without  
Conductor connection  
Connection method Screw connection with tension sleeve  
Conductor/PCB connection direction -90 °  
Conductor cross section rigid 0.2 mm² ... 2.5 mm²  
Conductor cross section flexible 0.2 mm² ... 2.5 mm²  
Conductor cross section AWG 24 ... 12  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²  
2 conductors with same cross section, solid 0.2 mm² ... 1 mm²  
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²  
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1 mm²  
2 conductors with the same cross section, flexible, w...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBW 2,5/11-ST-5,08 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.