

INDUSTRIAL COMPONENT DATA

PSC 1,5/ 5-F 1841912 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSC 1,5/ 5-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSC 1,5/ 5-F
Catalog number	1841912
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-26000D4E22
Generated	2026-07-28

Product Overview

Plug

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: PSC 1.5/.. -F, pitch: 3.5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, plug-in system: PSC 1.5, Electrical properties: shielded, locking: Screw lock, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1841912

Packing unit 50 pc

Catalog page Page 251 (C-1-2013)

GTIN 4017918111885

Weight per Piece (excluding packing) 7.340 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 16 mm

Width [w] 39.2 mm

Height [h] 12.5 mm

Pitch 3.5 mm

Dimension a 14 mm

General

Range of articles PSC 1,5/..-F

Number of positions 5

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V (for applications in metal or metal-plated housings, the degree of protection "safety extra-low voltage" must be used.)

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Maximum load current 8 A

Insulating material PA

Flammability rating according to UL 94 V0

Screw thread M2

Tightening torque, min 0.22 Nm

Tightening torque max 0.25 Nm

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, w...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSC 1,5/ 5-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.