

INDUSTRIAL COMPONENT DATA

PT 1,5/ 5-PH-5,0 CLIP 1755761 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 5-PH-5,0 CLIP



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 5-PH-5,0 CLIP
Catalog number	1755761
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-6162EA4622
Generated	2026-08-02

Product Overview

PCB terminal block

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 10 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of articles: PT 1.5/.. -PH CLIP, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping method: H1L Philipps-Recess with longitudinal groove, conductor connection direction/printed circuit board: 0 °, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1755761

Packing unit 100 pc

Note Made to Order (non-returnable)

Catalog page Page 425 (C-1-2013)

GTIN 4046356334945

Weight per Piece (excluding packing) 5.280 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [l] 14.7 mm

Width [w] 25 mm

Height [h] 12.3 mm

Pitch 5 mm

Dimension a 20 mm

General

Range of articles PT 1,5/..-PH CLIP

Number of positions 5

Connection method Screw connection with tension sleeve

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 10 A

Nominal cross section 1.5 mm²

Maximum load current 10 A

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 6 mm

Tightening torque, min 0.35 Nm

Tightening torque max 0.4 Nm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1 mm²

Conductor cross section AWG min. 26...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 5-PH-5,0 CLIP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.