

INDUSTRIAL COMPONENT DATA

PTS 1,5/ 7-PH-5,0 1805562 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTS 1,5/ 7-PH-5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTS 1,5/ 7-PH-5,0
Catalog number	1805562
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-CFC7BF2F6C
Generated	2026-08-01

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 10 A, nominal voltage (III/2): 400 V, contact surface: Tin, contact type: Female, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, family of articles: PTS 1.5/.. -PH, pitch: 5mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON PST 1.3, lock: without, fixing type: without, packaging type: boxed

Conductive plate connector, nominal cross-section: 1.5 mm², colour: green, nominal current: 10 A, reference voltage (III/2): 400 V, contact surface: Sn, contact type: Female connector, number of potentials: 7, number of rows: 1, number of poles: 7, number of connections: 7, item range: PTS 1.5/.. -PH, pitch: 5 mm, connection type: Push-in spring connection, conductor/PCB plugging direction: 0°, plug-in system: COMBICON PST 1.3, locking: without, fastening type: without, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1805562

Packing unit 100 pc

Note Made to Order (non-returnable)

Catalog page Page 417 (C-1-2013)

GTIN 4046356679978

Weight per Piece (excluding packing) 4.560 g

Custom tariff number 85366990

Country of origin BG (Bulgaria)

Dimensions

Length [l] 12.8 mm

Width [w] 35 mm

Height [h] 11.7 mm

Pitch 5 mm

Dimension a 30 mm

General

Range of articles PTS 1,5/...-PH

Number of positions 7

Connection method Push-in spring connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 400 V

Rated voltage (II/2) 600 V

Nominal current IN 10 A

Nominal cross section 1.5 mm²

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 8 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 14

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTS 1,5/ 7-PH-5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.