


**INDUSTRIAL COMPONENT DATA**

# QC 1/13-ST-5,08 1883815 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: QC 1/13-ST-5,08



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | PHOENIX CONTACT |
| MPN / Reference | QC 1/13-ST-5,08 |
| Catalog number  | 1883815         |
| Category        | Cable connector |
| Minimum order   | 50 Pcs          |
| Document ID     | EO-5F418DCB12   |
| Generated       | 2026-08-02      |

## Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1 mm<sup>2</sup>, color: green, nominal current: 10 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 13, number of rows: 1, number of poles: 13, number of connections: 13, family of articles: QC 1/. -ST, pitch: 5.08 mm, connection type: Offset connection, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 1883815

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 290 (C-1-2013)

GTIN 4017918157838

Weight per Piece (excluding packing) 22.110 g

Custom tariff number 85366990

Country of origin PL (Poland)

**Dimensions**

Length [ l ] 33.8 mm

Width [ w ] 66.86 mm

Height [ h ] 15 mm

Pitch 5.08 mm

Dimension a 60.96 mm

**General**

Range of articles QC 1/-ST

Number of positions 13

Connection method Displacement connection

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Nominal cross section 1 mm<sup>2</sup>Maximum load current 10 A (with 1 mm<sup>2</sup> conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

**Connection data**Conductor cross section flexible min. 0.5 mm<sup>2</sup>Conductor cross section flexible max. 1 mm<sup>2</sup>

Conductor cross section AWG min. 20

Conductor cross section AWG max. 18

Minimum AWG according to UL/CUL 22

Maximum AWG according to UL/CUL 18

Wire diameter incl. insulation 2.5 mm

**Standards and Regulations**

Connection in acc. with standard EN-VDE

**CUL**

Flammability rating according to UL 94 V0

**Environmental Product Compliance**

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**

eCl@ss 4.0272607xxeC...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QC 1/13-ST-5,08 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.