

INDUSTRIAL COMPONENT DATA

QC 1/ 4-ST-5,08 1883271 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: QC 1/ 4-ST-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	QC 1/ 4-ST-5,08
Catalog number	1883271
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-470BC9891B
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1 mm², color: green, nominal current: 10 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: QC 1/.. -ST, pitch: 5.08 mm, connection type: Offset connection, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross-section: 1 mm², colour: green, rated current: 10 A, dimensioning voltage (III/2): 630 V, contact surface: Sn, contact connection type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, product series: QC 1/.. -ST, pitch: 5.08 mm, connection type: insulation displacement connection, conductor/board connection direction: 0 °, locking hook: - Locking hook, plug system: COMBICON MSTB 2.5, locking: none, fixing type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1883271

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 290 (C-1-2013)

GTIN 4017918157739

Weight per Piece (excluding packing) 7.230 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 33.8 mm

Width [w] 21.14 mm

Height [h] 15 mm

Pitch 5.08 mm

Dimension a 15.24 mm

General

Range of articles QC 1/-ST

Number of positions 4

Connection method Displacement connection

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 10 A

Nominal cross section 1 mm²

Maximum load current 10 A (with 1 mm² conductor cross section)

Insulating material PA

Flammability rating according to UL 94 V0

Connection data

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 1 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 18

Minimum AWG according to UL/CUL 22

Maximum AWG according to UL/CUL 18

Wire diameter incl. insulation 2.5 mm

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QC 1/ 4-ST-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.