

INDUSTRIAL COMPONENT DATA

QC 1,5/ 4-ST 1717987 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: QC 1,5/ 4-ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	QC 1,5/ 4-ST
Catalog number	1717987
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-B4C04041DA
Generated	2026-07-29

Product Overview

Plug

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: QC 1.5/.. -ST, pitch: 5 mm, connection type: Offset connection, conductor/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross-section: 1.5 mm², color: green, rated current: 12 A, rated voltage (III/2): 630 V, contact surface: Sn, contact type: socket, number of potentials: 4, number of rows: 1, number of poles: 4, number of connectors: 4, article family: QC 1.5/.. -ST, Pitch: 5 mm, Connection type: Cutting connection, Connection direction conductor/board: 0 °, Locking hook: - Locking hook, Plug-in system: COMBICON MSTB 2.5, Locking: without, Fastening type: without, Packaging type: packed in a carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1717987

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 292 (C-1-2013)

GTIN 4046356140256

Weight per Piece (excluding packing) 11.840 g

Custom tariff number 85366990

Country of origin CN (China)

Dimensions

Length [l] 36.85 mm

Width [w] 21.4 mm

Height [h] 19.6 mm

Pitch 5 mm

Dimension a 15 mm

General

Range of articles QC 1,5/...-ST

Number of positions 4

Connection method Displacement connection

Insulating material group I

Rated surge voltage (III/3) 6 kV

Rated surge voltage (III/2) 6 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 500 V

Rated voltage (III/2) 630 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 1.5 mm²

Maximum load current 12 A

Insulating material PA

Flammability rating according to UL 94 V0

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 16

Minimum AWG according to UL/CUL 24

Maximum AWG according to UL/CUL 16

Wire diameter incl. insulation 3 mm

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above thresh...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QC 1,5/ 4-ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.