

**INDUSTRIAL COMPONENT DATA**

# SMSTB 2,5/13-ST-5,08 1826393 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SMSTB 2,5/13-ST-5,08



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | PHOENIX CONTACT      |
| MPN / Reference | SMSTB 2,5/13-ST-5,08 |
| Catalog number  | 1826393              |
| Category        | Cable connector      |
| Minimum order   | 50 Pcs               |
| Document ID     | EO-0FE22269BE        |
| Generated       | 2026-07-29           |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 13, number of rows: 1, number of poles: 13, number of connections: 13, family of articles: SMSTB 2.5/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: -45 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

### Additional Product Information

Key Commercial Data

Orderkey 1826393

Packing unit 50 pc

Catalog page Page 268 (C-1-2013)

GTIN 4017918122140

Weight per Piece (excluding packing) 23.500 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [ l ] 25.6 mm  
Width [ w ] 66.04 mm  
Height [ h ] 15.5 mm  
Pitch 5.08 mm  
Dimension a 60.96 mm  
General  
Range of articles SMSTB 2,5/...-ST  
Number of positions 13  
Connection method Screw connection with tension sleeve  
Insulating material group I  
Rated surge voltage (III/3) 4 kV  
Rated surge voltage (III/2) 4 kV  
Rated surge voltage (II/2) 4 kV  
Rated voltage (III/3) 250 V  
Rated voltage (III/2) 320 V  
Rated voltage (II/2) 630 V  
Connection in acc. with standard EN-VDE  
Nominal current I<sub>N</sub> 12 A  
Nominal cross section 2.5 mm<sup>2</sup>  
Maximum load current 12 A (with a 2.5 mm<sup>2</sup> conductor cross section)  
Insulating material PA  
Flammability rating according to UL 94 V0  
Internal cylindrical gage A3  
Stripping length 7 mm  
Screw thread M3  
Tightening torque, min 0.5 Nm  
Tightening torque max 0.6 Nm  
Connection data  
Conductor cross section solid min. 0.2 mm<sup>2</sup>  
Conductor cross section solid max. 2.5 mm<sup>2</sup>  
Conductor cross section flexible min. 0.2 mm<sup>2</sup>  
Conductor cross section flexible max. 2.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>  
Conductor cross section flexible, with ferrule with....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SMSTB 2,5/13-ST-5,08 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.