

**INDUSTRIAL COMPONENT DATA**

# TSPC 5/ 3-STF-7,62 1728219 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: TSPC 5/ 3-STF-7,62



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | PHOENIX CONTACT    |
| MPN / Reference | TSPC 5/ 3-STF-7,62 |
| Catalog number  | 1728219            |
| Category        | Cable connector    |
| Minimum order   | 50 Pcs             |
| Document ID     | EO-8EE3116DA5      |
| Generated       | 2026-07-28         |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 6 mm<sup>2</sup>, color: green, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 6, family of articles: TSPC 5/.. -STF, pitch: 7.62 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - without clamping hook, plug-in system: COMBICON PC 5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

### Additional Product Information

Key Commercial Data

Orderkey 1728219

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 533 (C-1-2013)

GTIN 4046356144582

Weight per Piece (excluding packing) 28.000 g

Custom tariff number 85366990

Country of origin BG (Bulgaria)

**Dimensions**

Length [ l ] 41.45 mm

Width [ w ] 38.08 mm

Height [ h ] 35.05 mm

Pitch 7.62 mm

Dimension a 15.24 mm

**General**

Range of articles TSPC 5/..-STF

Number of positions 3

Connection method Push-in spring connection

Insulating material group I

Rated surge voltage (III/3) 8 kV

Rated surge voltage (III/2) 8 kV

Rated surge voltage (II/2) 6 kV

Rated voltage (III/3) 1000 V

Rated voltage (III/2) 1000 V

Rated voltage (II/2) 1000 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 41 ANominal cross section 6 mm<sup>2</sup>

Maximum load current 41 A

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 15 mm

**Connection data**Conductor cross section solid min. 0.2 mm<sup>2</sup>Conductor cross section solid max. 10 mm<sup>2</sup>Conductor cross section flexible min. 0.2 mm<sup>2</sup>Conductor cross section flexible max. 6 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max....

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / TSPC 5/ 3-STF-7,62 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.