

INDUSTRIAL COMPONENT DATA

PP-H 4/14 3212093 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PP-H 4/14



Manufacturer	PHOENIX CONTACT
MPN / Reference	PP-H 4/14
Catalog number	3212093
Category	Terminal block connector
Minimum order	10 Pcs
Document ID	EO-3E2757DED7
Generated	2026-08-05

Product Overview

Plug

Connector, rated voltage: 800 V, rated current: 32 A, number of connections: 14, number of poles: 14, connection type: Push-in connection, 1st floor, left-hand connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 6 mm², color: gray Plug, nom. voltage: 800 V, nominal current: 32 A, number of connections: 14, number of positions: 14, connection method: Push-in connection, 1st level connection left, Rated cross section: 4 mm², cross section: 0.2 mm² - 6 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Technical dataProduct propertiesProduct type Terminal plug
Area of application Railway industry
Machine building
Plant engineering
Number of positions 14
Pitch 6.2 mm
Number of connections 14
Number of rows 1
Potentials 14
Data management status
Article revision 01
Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 8 kV

Maximum power dissipation for nominal condition 1.02 W

Connection data Number of connections per level 14

Nominal cross section 4 mm²

1st level connection left

Stripping length 10 mm ... 12 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 61984

Conductor cross section rigid 0.2 mm² ... 6 mm²

Cross section AWG 24 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 4 mm²

Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²

Nominal current 32 A

Maximum load current 32 A (with 6 mm² conductor cross section)

Nominal voltage 800 V

Nominal cross section 4 mm²

1st level connection left Connection cross sections directly pluggable

Conductor cross section rigid 0.5 mm² ... 6 mm²

Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm² ... 4 mm²

Flexible con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PP-H 4/14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.