


INDUSTRIAL COMPONENT DATA

UP 4-4VT 3208721 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: UP 4-4VT



Manufacturer	PHOENIX CONTACT
MPN / Reference	UP 4-4VT
Catalog number	3208721
Category	Test plug for terminal blocks
Minimum order	10 Pcs
Document ID	EO-DC211EE34A
Generated	2026-08-03

Product Overview

Plug

Connector for four voltage converters

Plug for four voltage transducers

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Technical dataProduct propertiesProduct type Plug

Number of positions 8

Number of connections 8

Number of rows 1

Potentials 8

Data management status

Article revision 05

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 4 kV

Maximum power dissipation for nominal condition 1.31 W

Connection dataNominal cross section 6 mm²

Rated cross section AWG 10

Level 1

Screw thread M3

Tightening torque 0.6 ... 0.8 Nm

Stripping length 8 mm ... 9 mm

Internal cylindrical gage A4

Connection in acc. with standard IEC 61984

Conductor cross section rigid 0.14 mm² ... 6 mm²

Cross section AWG 26 ... 10 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm² ... 6 mm²

Conductor cross section, flexible [AWG] 26 ... 10 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²

Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve) 0.5 mm² ... 2.5 mm²

2 conductors with same cross section, solid 0.14 mm² ... 1.5 mm²

2 conductors with the same cross-section AWG rigid 26 ... 16 (converted acc. to IEC)

2 conductors with same cross section, flexible 0.14 mm² ... 1.5 mm²

2 conductors with the same cross-section AWG flexible 26 ... 16 (converted acc. to IEC)

2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UP 4-4VT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.