

INDUSTRIAL COMPONENT DATA

REL-IR2/LDP- 60DC/2X21 2903662 PHOENIX CONTACT Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-IR2/LDP-60DC/2X21



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-IR2/LDP-60DC/2X21
Catalog number	2903662
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-D6594DC4A4
Generated	2026-08-05

Product Overview

Single relay

Plug-in industrial relays with power contacts, 2 inverter contacts, test key, status LED, free-flowing diode, mechanical switching position indication, A1+, A2- polarity, input voltage: 60 V DC

Industrial plug-in relays with power contacts, 2 changeover contacts, test button, status LED, damping diode, mechanical status signal, polarity A1+, A2-, input voltage: 60 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2903662

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 292 (C-7-2013)

GTIN 4046356758154

Weight per Piece (excluding packing) 35.400 g

Custom tariff number 85364190

Country of origin PL (Poland)

Dimensions

Width 21.2 mm

Height 27.5 mm

Depth 35.6 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 60 V DC

Input voltage range in reference to UN see diagram

Typical input current at UN 18 mA

Typical response time 13 ms

Typical release time 14 ms

Protective circuit Damping diode

Status display Yellow LED

Power dissipation for nominal condition 1.08 W

Contact side

Contact type 2 PDT

Type of switch contact Single contact

Contact material AgNi

Maximum switching voltage 250 V AC/DC

Minimum switching voltage 5 V (At 24 mA)

Min. switching current 5 mA (at 24 V)

Maximum inrush current 30 A (20 ms, N/O contact)

Limiting continuous current 12 A

Interrupting rating (ohmic load) max. 288 W (at 24 V DC)

124 W (at 48 V DC)

108 W (at 60 V DC)

52 W (at 110 V DC)

48 W (at 220 V DC)

3000 VA (for 250 V AC)

Switching capacity min. 0.12 W

Motor load according to UL 508 1/2 HP, 240 V AC

General

Test voltage relay winding/relay contact 2.5 kVrms(50 Hz, 1 min.)

Test voltage relay contact/relay contact 2.5 kVrms(50 Hz, 1 min.)

Test voltage PDT/PDT 2.5 kVrms(50 Hz, 1 min.)

Operating mode 100% operating factor

Degree of protection RT I

Mechanical se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-IR2/LDP-60DC/2X21 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.