

INDUSTRIAL COMPONENT DATA

REL-IR4/LDP- 48DC/4X21AU 2903671 PHOENIX CONTACT

Single relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: REL-IR4/LDP-48DC/4X21AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	REL-IR4/LDP-48DC/4X21AU
Catalog number	2903671
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-846CBC002E
Generated	2026-08-05

Product Overview

Single relay

Plug-in industrial relays with power contacts and additional hard gold, 4 inverter contacts, test key, status LED, free-flowing diode, mechanical indication of switching position, polarity A1+, A2-, coil voltage: 48 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data

Orderkey 2903671

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 292 (C-7-2013)

GTIN 4046356758840

Weight per Piece (excluding packing) 35.600 g

Custom tariff number 85364190

Country of origin PL (Poland)

Dimensions

Width 21.2 mm

Height 27.5 mm

Depth 35.6 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Coil side

Nominal input voltage UN 48 V DC

Input voltage range in reference to UN see diagram

Typical input current at UN 22 mA

Typical response time 13 ms

Typical release time 14 ms

Protective circuit Damping diode

Status display Yellow LED

Power dissipation for nominal condition 1.06 W

Contact side

Contact type 4 PDTs

Type of switch contact Single contact

Contact material AgNi, hard gold-plated

Note If the specified maximum values for multi-layer contact relays are exceeded, the gold plating is destroyed. The maximum values of the power contact relay are then valid. This can result in a shorter service life than with a pure power contact.

Maximum switching voltage 30 V AC

36 V DC

Minimum switching voltage 2 V (At 24 mA)

Min. switching current 2 mA (24 V DC)

Maximum inrush current 50 mA

Limiting continuous current 50 mA

Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)

Switching capacity min. 48 mW

Motor load according to UL 508 1/3 HP, 240 V AC

Contact side (with destroyed gold layer)

Contact material AgNi

Note the following values are applicable if a....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / REL-IR4/LDP-48DC/4X21AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.