


INDUSTRIAL COMPONENT DATA

HCC 4-MC 1660669 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCC 4-MC



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCC 4-MC
Catalog number	1660669
Category	Terminal block connector
Minimum order	1 Pcs
Document ID	EO-745C16540A
Generated	2026-08-01

Product Overview

Plug

Plug-in part, rated voltage: 400 V, rated current: 13.5 A, number of connections: 10, connection type: Crimped connection, Sizing cross-section: 1.5 mm², cross-section: 0.2 mm² - 4 mm², mounting class: direct screwed, color: gray
Plug, nom. voltage: 400 V, nominal current: 13.5 A, number of connections: 10, connection method: Crimp connection, Rated cross section: 1.5 mm², cross section: 0.2 mm² - 4 mm², mounting type: direct screw connection, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type High current terminal block

Number of connections 10

Number of rows 1

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 6 kV

Maximum power dissipation for nominal condition 0.77 W

Connection dataNumber of connections per level 10

Nominal cross section 2.5 mm²

Connection in acc. with standard IEC 61984

Conductor cross section rigid 0.2 mm² ... 4 mm²

Cross section AWG 24 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 24 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 4 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 4 mm²
2 conductors with same cross section, solid 0.2 mm² ... 2.5 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 2.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 2.5 mm²
Nominal current 13.5 A
Maximum load current 13.5 A (with STG-MTN 0,5-1,0 contact)
20 A (with STG-MTN 1,5-2,5 contact)
Nominal voltage 400 V
Nominal cross section 1.5 mm²
Dimensions Width 92 mm
Height 34.6 mm
Depth 17 mm
Drill hole spacing 83 mm
Material specifications Color gray (RAL 7042)
Flammability rating according to UL 94 V2
Insulating materi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCC 4-MC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.