

INDUSTRIAL COMPONENT DATA

PP-H 1,5/S/10 3212594 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PP-H 1,5/S/10



Manufacturer	PHOENIX CONTACT
MPN / Reference	PP-H 1,5/S/10
Catalog number	3212594
Category	Terminal block connector
Minimum order	25 Pcs
Document ID	EO-DF06B6A64C
Generated	2026-08-03

Product Overview

Plug

Connector, rated voltage: 500 V, rated current: 17.5 A, number of connections: 10, number of poles: 10, connection type: Push-in connection, 1st floor, Sizing cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3212594

Packing unit 25 pc

Minimum order quantity 25 pc

Catalog page Page 284 (C-1-2017)

GTIN 4046356565738

Weight per Piece (excluding packing) 16.850 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Number of positions 10

Number of levels 1

Number of connections 10

Potentials 10

Nominal cross section 1.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Maximum load current 17.5 A (with 1.5 mm² conductor cross section)
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.56 W
Maximum load current 17.5 A (with 1.5 mm² conductor cross section)
Nominal current I_N 17.5 A (observe derating)
Nominal voltage U_N 500 V
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (AST...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PP-H 1,5/S/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.